

Grooved Edge Zuri Quick Reference Guide

COLORS: Weathered Gray, Pecan, Walnut, Brazilia, Chestnut & Hickory

BOARD SIZES: 5/4" Thick x 6" Wide x 12', 16' & 20' Lengths **TRIM SIZE:** 5/4" Thick x 3-1/2" Wide x 2" Height x 12' Length

FASCIA: 3/4" Thick x 7-1/4" Wide x 12' Length and 3/4" Thick x 11-1/4" Wide x 12' Length JOIST SPACING: Minimum of 3-1/2" Joist Height & All Framing/Sleepers must be Anchored

16" OC - Residential Perpendicular Installation (12" OC Recommended for Wood like Stiffness)

12" OC - Heavy Traffic or Commercial Installs & 45° or Herringbone Layout

12" OC - All Stair/Step Stringers

INSTALLATION PROGRESSION: For Best Results, Zuri Must be Installed in the Proper Sequence

- 1) Main Body Deck Skirt Board
- 2) Main Body Deck Trim Picture Frame Perimeter of Main Deck with Trim Board
- 3) Main Body of Decking Inlay Field of Decking, Working Towards the Structure
- 4) Steps and Landings Complete the Steps & Landings Using Same Procedures Outlined Above

COLOR MATCHED END COAT PAINT: 1 Bottle Coats Approximately 140 Ends & 2 Bottles per Job Minimum

Weathered Gray - Sherwin Williams - 2840 Hammered Silver

Pecan - Sherwin Williams - 1112 Setter's Coat Walnut - Sherwin Williams - 1112 Setter's Coat Brazilia - Sherwin Williams - 6062 Rugged Brown Chestnut - Sherwin Williams - 6117 Smokey Topaz Hickory - Sherwin Williams - 6076 Turkish Coffee

HEADCOTE CAP-TOR SCREWS: #10 x 2-1/2" - Install in Vertical Surface of Trim & Face Fastener as Needed

Weathered Gray - Tan Gray #31

Pecan - Cedar #8 Walnut - Brown #34 Brazilia - Mahogany #82 Chestnut - Buckskin #63 Hickory - Java #73

NOTE: 305 Stainless for Inland Builds & 316 Stainless for Coastal Applications

(Estimate 1 Screw/LF of Trim)

(Estimate 3 Screws)

(100, 350, 1,050 & 1,750 Count Boxes)

GROOVED ZURI CLIPS & FASTENERS:

Clip Spacing Sizes: 2-1/4" Torx Screw (316 Stainless) Threaded into a High-Density Plastic Clip

- 3/32" Spacing Most Popular and Common Spacing
- 3/16" Spacing Recommended for Areas Prone to High Debris, High Moisture or Low Ventilation

Fastener Packaging: Only Two Options Available for Clip Quantities, Box or Bucket

• 90 Count Box - Includes (1) #15 Torx Bit

Covers 45 SF @ 12" OC Framing & 50 SF @ 16" OC Framing

• 900 Count Bucket - Includes (3) #15 Torx Bits

Covers 450 SF @ 12" OC Framing & 500 SF @ 16" OC Framing

INSTALLATION VIDEOS: https://www.youtube.com & Search "Zuri Premium Decking by Royal" for 5 Videos

INSTALLATION CHECKLIST: Materials, Tools & Accessories Required for Every Zuri Deck Installation

- Zuri Deck Boards & Trim Cap
- Color Matched End Coat Paint
- Headcote Cap-Tor Screws
- Grooved Zuri Clips & Fasteners
- 2P-10 Activator & Adhesive (Only for Gluing Miters on Zuri Trim)
- Heavy Duty Clear PVC Cement (Only for Gluing Miters on Zuri Trim)
- Schedule Royal's 1st Nail 1st Board Installation Training

